

Technical University of Denmark



Generalized Phase Contrast with matched filtering using LCoS pico-projectors

Bañas, Andrew Rafael; Palima, Darwin; Glückstad, Jesper

Published in:
8th EOS Topical Meeting on Diffractive Optics

Publication date:
2012

Document Version
Publisher's PDF, also known as Version of record

[Link back to DTU Orbit](#)

Citation (APA):
Bañas, A. R., Palima, D., & Glückstad, J. (2012). Generalized Phase Contrast with matched filtering using LCoS pico-projectors. In 8th EOS Topical Meeting on Diffractive Optics: DO2012 Technical digest European Optical Society.

DTU Library

Technical Information Center of Denmark

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

Generalized Phase Contrast with matched filtering using LCoS pico-projectors

Andrew Bañas, Darwin Palima and Jesper Glückstad

*DTU Fotonik, Department of Photonics Engineering
Programmable Phase Optics
Technical University of Denmark
DK-2800 Kgs. Lyngby, Denmark
www.ppo.dk*

We report a beam shaping system for generating high intensity programmable optical spots using mGPC: matched filtering combined with Generalized Phase Contrast applying two consumer handheld pico-projectors. Such a system presents a low cost alternative for optical trapping and manipulation, optical lattices and other beam shaping applications usually implemented with high-end spatial light modulators. Portable pico-projectors based on liquid crystal on silicon (LCoS) devices were used as binary phase-only spatial light modulators by setting the appropriate polarization of the illumination. They were subsequently placed into the object and Fourier plane of a 4f-setup based on the mGPC configuration. Having a dynamic spatial phase filter, instead of a fabricated one, allows the beam shaper to adapt to different input phase patterns suited for different requirements. Despite imperfections in these consumer pico-projector LCoS-devices, the mGPC approach tolerates phase aberrations that would have otherwise been contrasted by a standard phase imaging technique.